

# USING AN ADVANCED DISCRETE-EVENT SIMULATION FRAMEWORK TO PRODUCTIVE CAPACITY MANAGEMENT OF A CAR-PARTS FACTORY

Adrián M. Aguirre <sup>(a)</sup>, Enrique J. Müller <sup>(b)</sup>, Sebastián E. Seffino <sup>(c)</sup>, Carlos A. Méndez <sup>(d)</sup>

<sup>(a),(b),(c)</sup> Industrial Engineering Department (FIQ-UNL), Santiago del Estero 2829, 3000 Santa Fe, Argentina.  
<sup>(d)</sup> INTEC (UNL -CONICET), Güemes 3450, 3000 Santa Fe, Argentina.

<sup>(a)</sup> [aguirreadrianmarcelo@hotmail.com](mailto:aguirreadrianmarcelo@hotmail.com), <sup>(b)</sup> [enriquejmuller@hotmail.com](mailto:enriquejmuller@hotmail.com), <sup>(c)</sup> [aseffino@hotmail.com](mailto:aseffino@hotmail.com),  
<sup>(d)</sup> [cmendez@intec.unl.edu.ar](mailto:cmendez@intec.unl.edu.ar)

## ABSTRACT

This work presents the development and application of an advanced modelling, simulation and optimization framework focused on the production process of car-parts factory in the Latin-American market. Lying on the concepts of the process-interaction approach, the principal components available in the discrete event simulation environment “SIMUL8” were used to achieve the best representation of the large and complex manufacturing system. Furthermore, advanced SIMUL8’s Visual Logic tools were utilized for modelling specific design and operation features arising in the process under study. The developed tool provides a valuable support system for making and testing operative, tactical and strategic decisions, allowing a quick evaluation of possible sceneries ranging from different operation schemes to potential alternatives of investment. The principal aim of this work is to provide a systematic methodology to validate, evaluate and improve the productive capacity management, enhancing both the process profitability and the degree of customer satisfaction.

Keywords: discrete-event simulation, manufacturing process, SIMUL8, process-interaction approach

## 1. INTRODUCTION

During the last years Argentina's economic growth was more than twice that of Bolivia, Brazil, Chile and Paraguay, becoming one of the leaders in the region, with major improvements in employment and income distribution and a decline in poverty levels. Within this economic positive context, the automotive industry has been directly affected with a significant increase in car sales and an increasing demand of car-parts. To take advantage of this opportunity, manufacturing plants related to the automotive business are being enforced to improve their process productive capacity. In this work we addressed the particular problem arising in a Company, dedicated to manufacture a high volume and variety of car-parts in Argentina. The major project goals aims at increasing the process productivity and the customer satisfaction.

In order to turn the company more profitable and competitive in a highly demanding market, it was observed the need to rely on effective computational tools to systematically analyze and evaluate the dynamic behaviour of the process, considering different operative schemes and possible alternatives of investment.

Although the use of mixed-integer linear mathematical programming models (MILP) was considered in a preliminary stage of the project, the idea was quickly abandoned due to the lack of proper tools to manage large problem sizes, complex operational logic and different degrees of uncertainty in the problem data. In consequence, discrete events simulation methods were adopted to represent the whole real-world process in an integrated form. In this way, it was possible to clearly identify the problematic situations, providing validated answers to operative, tactical and strategic level requirements involving different sceneries and possible alternatives of investment. Similar applications based on simulation technology to the treatment of operative schemes and alternative of investment in the petrochemical industry can be found in Bacigalupo C.M et al. (2006).

This paper is organized as follows. Section 2 introduces the company under study and the problem to be addressed. The proposed simulation-based methodology is presented in Section 3, describing the steps followed in the model development, the system limitations, the embedded system logic and the user interfaces. Finally, Section 4 introduces some suggested sceneries to give response to the problem challenges and defines the performance indicators to be considered to the study of the system.

## 2. PROBLEM DEFINITION

### 2.1. The Company

The main industrial activity of the Company is the manufacturing of a wide variety and a large volume of a basic element of the internal combustion engine, which are commercialized in different markets in a broad range of measures and applications, and under the most

rigorous standards of quality. Currently, the company employs more than 50 people to reach a productive capacity of approximately 600.000 pieces monthly. Its present business volume and its integrated manufacturing system allow them to be among the three main car-parts factories in South America, reaching to export 52% of its production, almost totally to different Mercosur countries.

The manufacturing process comprises two different production lines and twelve processing stages depending on the main raw materials that are being used, i.e. bars or pipes. The company's policy is to meet the production orders arriving monthly at the time and the form that were previously agreed with the customers. To this end, the process is operated by selecting suitable small and medium production lots.

## 2.2. Main problems issues

At the present time, the constant raise of car-parts demand has motivated to the general managers of the company to improve the low process productivity associated with three main issues: a) low degree of customer satisfaction because of tardiness, b) large volume of work-in process inventory and (c) work-load unbalance of the manufacturing lines. The combination of these issues generates an inefficient utilization of the limited production resources available to attend the higher demand. Based on the foregoing issues, it were defined a series of challenges directly focused on the actual needs of the company: a) to increase the productivity of manufacturing lines and, b) to respond in more agile and reliable form to the customer requirements.

In summary, the general goal is oriented to optimize the current productive capacity of the company in such a way that most of the deliveries can be met on time and in the right form. In addition, it is desired to be in position of quickly reacting to different commitments in a future with uncertain and variable conditions. Based on the current trend of the economy and the increasing car-parts demand, the company should be able to expand its productive capacity to at least 1.000.000 pieces per month, which constitute the biggest challenge for this work.

## 2.3. Solution alternatives

Different available solution alternatives were evaluated to cope with this problem. The use of an analytical method based on linear mathematical formulation tools (MILP models), which are broadly used to production optimization, was avoided because of the inherent computational and modelling limitations of these techniques. Also, the use of simple heuristic procedures was considered but they failed to handle the high complexity of the problem. Although these two approaches may be valid to generate optimal solutions for the system, they are not capable of effectively managing the random nature of many process variables (e.g. processing time distributions, material movement time distributions, etc.), the large number of resources

involved and the complex operational rules to be considered. In order to overcome the limitations previously stated, it was decided to make use of a modern and user-friendly system analysis tool by developing an advanced computational process modeling on the notion of discrete event system simulation (Barcelo 1996; Banks et al. 2004; Koshnevis 1994)

## 2.4. Advantages of simulation-based methods

The main advantage of the proposed computer-aided methodology is that it permits to systematically reproduce the complex company process in an abstract and integrated form, visualizing the dynamic behaviour of its constitutive elements over time.

Production facilities (work centers), storage facilities (tails of waits, deposits of raw materials, intermediate storages and process storages), transports and materials movement devices (vehicles, bridge cranes, etc), external factors (variability in the arrival of the raw materials and demands), internal and unforeseen factors (changes in policies and operational rules, breaks, stops and maintenances of processing units in the production lines), and resources of the system (e.g. workers), were analyzed and modelled in detail. As result, a basic model was generated to discern the principal weaknesses and bottlenecks of the process, but it was also useful later for making decisions to enhance the current process performance.

## 3. THE PROPOSED SIMULATION-BASED FRAMEWORK

In order to formulate a precise computer-aided representation to the real-world manufacturing system described above, it was decided to make use of the simulation, visualization and analysis tool set provided in the discrete events simulation environment "SIMUL8" (Shalliker et al. 2002; Haige et al. 2001; Mc Gregor et al. 2004; SIMUL8 2004). The main characteristics of the proposed basic model are described in detail below.

### 3.1. Principal model features

- Raw Materials: depending on the raw material being used in the process (pipes or bars), two alternative manufacturing lines were modeled. The main raw material characteristics are detailed in the Table 1.

Table 1: Raw Materials Types

Raw material	Outside diameter [mm]	Length [meters]
bars	22 – 60	5.5 – 6
pipes	16 - 28.6	6

- Product Family: three main final product types were identified according to the principal characteristics of the process (see Table 2).

Table 2: Final Product Types

Product family	Characteristics
Small car-parts	Outside diameter <25,4[mm]
Medium car-parts	Outside diameter <38,1[mm]
Big car-parts	Outside diameter <60,3[mm]

- Manufacturing process stages: The production sequence for every car-part family depends on the raw material being used. The general manufacturing stages are listed in Table 3 whereas the specific product recipes for every car-part family and raw material are shown in Table 4 and Figure 1. In turn, the entire simulation model developed in the SIMUL8 environment can be found in Figure 2. Additionally, a partial size view of the in-progress SIMUL8 model can be seen in Figure 3.

Table 3: General Manufacturing Process Stages

Process stage	Description	Available units
0	Raw material reception	-
1	Bars cutting process	3 (cutting machines)
2	Re-cooking process	3 (ovens)
3	Soaping process	7 (vats)
4	Pressing process	6 (press)
5	Uncovering process	2 (press)
6	Rectifying process	2 (machines)
7	Cutting and beveling process	4 (machines)
8	Thermal treatment process	12 (vats)
9	Final rectifying process	4 (machines)
10	Pipe cutting process	1 (cutting machine)
11	Stamping process	2 (stamping machines)
12	Final control	(manual process)

Table 4: Process Sequence for Each Product Family

Family	Raw material	Production sequence (stages)
Small car-parts	Bars	0-1-2-3-4-5-2-3-4-6-7-11-8-9-12
Medium car-parts	Bars	0-1-2-3-4-5-2-3-4-6-7-8-9-12
Big car-parts	Bars	0-1-2-3-4-5-2-3-4-6-7-8-9-12
Small car-parts	Pipes	0-10-11-6-8-9-12
Medium car-parts	Pipes	0-10-11-6-8-9-12

- Lot-sizing: Every order of product is divided into a number of batches for its processing and

movement inside the factory. The maximum allowable batch size is defined in Table 5. This limitation comes mainly from the maximum feasible processing load and the available capacity of material handling resources.

Table 5: Maximum Batch Size for Each Product Type

Small car-part	Medium car-part	Big car-part
2500	1500	500

- Shift timetable: Three 8-hour work shifts are contemplated from Monday to Saturday. Also, an additional shift for Sunday is defined. The same ones are detailed in Table 6.

Table 6: Shift Timetable

Shift	Start time [hrs]	End time [hrs]	Days
Morning	6:00	14:00	Mon - Sat
Afternoon	14:00	22:00	Mon - Sat
Night	22:00	6:00	Mon - Fri
Sunday	6:00	14:00	Sun

- Resources of the System: Available resources for storage in transit, temporary storage and movement of materials are detailed in Table 7.

Table 7: Available Production Resources in the Factory

Resource name	Description	Quantity available
Baskets	Resource for the storage in process	150
Pots	Resource for the storage in process	50
Soaping baskets	Resource for the storage in process	6
Cages	Resource for the storage in process	50
Hydraulic elevators	Manual vehicle for materials handling	5
Bridge crane	Device for materials handling	1
Manual Vehicles	Manual vehicle for materials handling	2
Hoist	Vehicle for materials handling	1
Conveyors	Device for materials handling	10

- Available manpower: The workers were modeled as an additional manufacturing resource in the production system with a dynamic availability over time. The allocation of workers to processing stages depends directly on the work shift and it is detailed in Table 8. In addition, programmed and non-programmed breaks and absenteeism can be easily incorporated in the simulation model.

Tabla 8: Dynamic Manpower Availability in the Factory

Resource name (Workers)	Processing stages	Worker availability for each work shift			
		Morning	Afternoon	Night	Sunday
Cut worker of bars	1	1	1	1	0
Re-cook worker	2-3	1	1	1	1
Maintenance worker	all	2	2	2	2
Press worker	4-5	4	4	3	3
Rectified, cut and beveled worker	6-7	3	4	3	0
Thermal treatment worker	8	4	4	4	0
Final rectified worker	9	4	4	0	0
Final control worker	12	5	5	0	0
Worker of pipes	10-11-6-8-9	1	1	0	0

- Data modeling: The processing time of the principal units was modeled using a normal probability distribution, which depends on the product type, the operation stage and the characteristic of the raw material that is being used (i.e. outside diameter). The validated parameters of the distribution were obtained after conducting the corresponding statistics studies. Likewise, two different setup times were modeled using deterministic values. The first one depends on the changes in product type and the current operation process. The second one was modeled for changes in process operations, i.e. for multipurpose units. These conditions were carefully programmed by using SIMUL8's Visual Logic functions (VL) for each distribution. Also, uniform time distributions for materials movements and loading and unloading of materials in process were employed.

### 3.2. Model development and operative rules

Through the development of the simulation model, it were identified all the manufacturing restrictions and operational rules to be considered. These type of restrictions can be caused by operative intrinsic factors (e.g. maximum batch sizes for every car-part family, available manpower in each work shift, process operations and manufacturing stages allowed in each work center, etc.) as well as external factors (e.g. raw material shortfalls, demand variability, etc.).

These features were directly modelled by using the Visual Logic function (VL) available in the SIMUL8 software, based on the occurrence of different system events. An illustrative example for the embedded logic behind the order priority definition is shown Figure 4. Other actual manufacturing restrictions and operating rules are described below.

1. Production batch sizes are based on the maximum capacity defined for every product type. The selected size is maintained through the entire production process, comprising processing stages and material movements).

2. The material movement activities have higher priority than any other processing activity.
3. Processing units are modelled as unary resources, i.e. batches are processed one by one in every work center, except in certain centers like ovens. In these manufacturing resources, two batches must be processed simultaneously. Each oven can perform two operations (1st re-cooked and 2nd re-cooked). In every work load, it can be mixed batches of different product types but not batches of different operations.
4. Some facilities can perform several operations on different product types (multipurpose units). For example, some presses are able to carry out three operations for every product type whereas the ovens can perform two operations (1st re-cooked and 2nd re-cooked). Each kind of operation has a different processing time and setup time distributions. In consequence, tasks allocations for every product type at every work center are carefully managed in such a way that setup times can be minimized.
5. Raw materials (pipes and bars) are classified into several subtypes depending on the outside diameter. In order produce a particular order, it must be guaranteed the use of those subtypes (pipes or bars) in which the outside diameter is equal or larger than the diameter of the order. In case that at some time there is no availability of raw materials satisfying the outside diameter, the beginning of order must delayed up to the reception of the corresponding supply of material.
6. In every manufacturing stage, the processing of production orders is arranged depending on the predefined commercial priority.

7. In the case that all resources for material storage were totally busy, the model does not allow the assignment of resources to certain work centers in order to avoid any resource blockade.

In the same way, a series of dialogs and menus were developed by using Visual Basic tools in order to provide an interactive and user-friendly model interface. These tools allow the user to enter all the problem data and also to propose changes to the design and operative conditions of the production system. Moreover, it provides an effective way to analyze and study model results during the simulation run (see Figures 5 to 9).

Once the problem data was loaded in the simulator interfaces and the restrictions and operational rules were correctly programmed, it was possible to perform the validation of the simulation model in order to guarantee that the model imitates the current process conditions. Also, it was carefully observed if the model was slightly sensitive to superfluous changes in the system.

To do this, it was defined and analyzed a set of measures and indicators of performance and effectiveness in order to corroborate the correct computational representation of the real system. Total production volume, fulfilment of production goals, average amount of in-process inventory in every manufacturing stage were some of the system output variables that were analyzed in detail.

The study of the dynamic behaviour of certain system resources, such as machines, storage resources, workers and in-process inventory levels in each stage, was carried out using different SIMUL8 visual tools oriented to system output analysis (see Figure 8 and 9).

On the basis of the simulation results, it was possible to conclude that the development of the analyzed and validated basic model was useful in a preliminary project stage to identify the possible weak points in the manufacturing lines and to visualize the complex dynamic of global process.

This basic model is the principal tool for the study and analysis of alternative system solutions. In addition, it represents a suitable model to evaluate future decisions that could improve the proposed criterion as well as to propose better solutions that help to increase the current process performance.

#### 4. CONDUCTING SIMULATION STUDIES

After identifying the major operational issues in the process, it was proposed a series of changes related to design and operative features, which a priori could increase the productive capacity of the company and fix the weak points of the process.

To do this, alternative sceneries are to be generated, identifying the values of the factors that are considered to be more relevant. Some of them are explicitly defined below.

- Increasing the available capacity of the resources associated with the material movement.

- Increasing the existing manufacturing resources in the likely bottlenecks.
- Reassignment and dynamic re-scheduling of available workers and resources of the system.
- Increasing the number of machines in the principal process stages.
- Modification of some basic operative rules:
- Order sequencing in shared manufacturing resources (e.g. minimizing the number of setup times for work center, pre-assignment of tasks and products to be processing in every work center, modification in the processing sequence, etc.).

#### 4.1. Measures of Effectiveness

Our primary measures of effectiveness and performances are the following ones:

- Production volume per type of product (car-parts/Week or Pieces/Month).
- Production volume in every work center (car-parts/Week or Pieces/Month).
- Percentages of utilization of workers, work centers and resources of the system.
- Average in-process inventory in every stage

#### 5. CONCLUSIONS

This work presented the major steps followed for the development and the application of an advanced modelling, simulation and optimization tool to productive capacity management of a factory of a basic element of the internal combustion engine. It allows to easily represent and validate the existing operative schemes in the company in order to determine the weak points in the manufacturing lines that need to be improved. In addition, the developed tool can be used to analyse, test and predict the dynamic behaviour of the system after introducing modifications in the production schemes and/or possible alternatives of investment.

#### ACKNOWLEDGMENTS

The authors are thankful for financial support from FONCYT-ANPCyT under Grant PICT-01837, from CONICET under Grant PIP-5729 and from Universidad Nacional del Litoral under CAI+D 003-13.

#### REFERENCES

- Bacigalupo, C.M, Gratti, C.A, Martinez, A.O, Franzece, L.A, Fiorini, M.M, Paz, D.P., 2006. *Simulación computacional de la cadena logística de la refinería San Lorenzo*, Revista del Instituto Argentino del Petróleo. Available from: <http://www.paragontech.com.ar> [accessed 1 March 2008].
- Barceló, J., 1996. *Simulación de Sistemas discretos*. España., Isdefe.
- Banks, J., Carson, J, Nelson, B y Nicol, D., 2004. *Discrete event system simulation*, Fourth edition. USA, Prentice-Hall.

Koshnevis, B., 1994. *Discrete systems simulation*. USA, McGraw-Hill.

Law, M. and Kelton, W., 1991. *Simulation modeling and analysis*. USA, McGraw-Hill.

Shalliker, J., Ricketts, C., 2002. *An Introduction to SIMUL8*. Release nine. School of Mathematics and Statistics, University of Plymouth.

SIMUL8: Manual and User Guide. 2004. Visual Thinking International: Mississauga, Ontario Canada.

Haige, J.W. and Paige, K.N., 2001. *Learning SIMUL8: The Complete Guide*. Plain Vu: Bellingham, WA.

Mc Gregor, D.W, Cain, M.J., 2004. *An introduction to SIMUL8*. Department of Management, College of Business and Economics, University of Canterbury, New Zealand.




Figure 1. Global Manufacturing System of the Company




Figure 2. Computer-based Representation of the Entire Manufacturing Process Model Generated in the SIMUL8 Environment




Figure 3. Partial Size View of the In-progress SIMUL8 Model




Figure 4. Representation of Operative Rules Through SIMUL8's Visual Logic Programming



**SIMULATION MODEL DATA**

PRODUCTION PROCESS INFORMATION



PRODUCTION ORDERS

MANUFACTURING RESOURCES

OPERATIVE RULES

ALTERNATIVE DESIGN

Back Next Cancel

Figure 5: Principal Menu


**ORDER DATA**

ORDER INFORMATION

Order number  
1

Batch size [pieces]  
31000

Outside diameter [mm]  
25



Commercial priority

NONE PRIORITY  
 LOW PRIORITY  
 MEDIUM PRIORITY  
 HIGH PRIORITY  
 VERY HIGH PRIORITY

Type of raw material  
BARS

ADDITIONAL INFORMATION

Back Next Cancel


Figure 6: Interface Order Data

**ADDITIONAL INFORMATION**

ORDER\_ADDITIONAL INFORMATION

Id\_Order  
2544

Due Date [mm/dd/yy]  
03/27/08



Id\_Customer  
356

Customer information  
MAHLE

Back Finish Cancel

Figure 7: Interface for Detailed Order Information




Figure 8: Dynamic Evolution of Manufacturing Resource Utilization Along the Simulation




Figure 9: Dynamic Evolution of the In-process Inventory Level of “queue big pieces Op1” in the Pressing Stage.